



Main

Product or component type	Contactor
Range of product	TeSys N
Contactor application	Non-reversing
NEMA size	0
Motor power hp	3 hp 230 V AC 5 hp 460 V AC 5 hp 575 V AC 3 hp 200 V AC
NEMA degree of protection	Not rated (open device)
Control circuit	Common control circuit
[Uc] control circuit voltage	240 V AC
Auxiliary contact composition	1 NO + 1 NC
Poles description	3P
Phase	3 phases
Line Rated Current	18 A
Product certifications	CE CSA UL listed
System Voltage	600 V AC
Electrical connection	Screw clamp terminals

Complementary

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.