




---

 PRODUCT-DETAILS

# ACS355-01E-07A5-2

## LV AC machinery drive module, IEC: Pn 1.5 kW, 7.5 A (ACS355-01E-07A5-2)




---

**General Information**

Global Commercial Alias	ACS355-01E-07A5-2
Product ID	3AUA0000058169
ABB Type Designation	ACS355-01E-07A5-2
EAN	6438177223443
Catalog Description	LV AC machinery drive module, IEC: Pn 1.5 kW, 7.5 A (ACS355-01E-07A5-2)

Long Description	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for <u>speed and torque control of AC induction and permanent magnet motors.</u></p>
------------------	---

---

**Ordering**

Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS355-01E-07A5-2 Pn 1,5kW, I2n 7,5A IP20
Made To Order	No
Minimum Order Quantity	1 piece

Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

### Dimensions

Product Net Weight	2.2 kg
Product Net Depth / Length	217 mm
Product Net Height	344 mm
Product Net Width	132 mm
Package Level 1 Depth / Length	335 mm
Package Level 1 Height	160 mm
Package Level 1 Width	211 mm
Package Level 1 Units	1 carton

### Certificates and Declarations

Declaration of Conformity - CE	3AXD10000499279
REACH Date	20240905
REACH Declaration	9AKK107992A7060
REACH Information	True - contains substances > 0.1 mass percentage
RoHS Date	20230303
RoHS Information	3AXD10000499279
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

### Technical

Number of Phases	1
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Multiple Battery Information	No battery / cell included
Frequency (f)	50/60 Hz
Frame Size	R2
Input Voltage (U <sub>in</sub> )	200 ... 240 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS LON DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	Without control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1

Number of Digital In/Outputs	5/1
Output Current, Normal Use ( $I_n$ )	7.5 A
Output Power, Normal Use ( $P_n$ )	1.5 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	1.5 kW
	79 W
Ecodesign Exemption	Energy efficiency data is not provided for the 1~230 V drives. The drives with one phase input are not in the scope of the EU ecodesign requirements (Regulation EU/2019/1781).

**External Classifications and Standards**

ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

**Environmental**

SCIP	A0C930BD-63DB-45DE-AD8C-2B14E7FC2793 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

**Additional Information**

Product Name	Frequency converter
--------------	---------------------

**Where Used (as part of "kit")**

Identifier	Description	Type
3AUA0000157175		Kit

**Categories**

Drives → Low Voltage AC Drives → Machinery Drives → ACS355 - Machinery Drive

