



SIMATIC ET 200SP, server module for BaseCarrier pack quantity: 1 unit,

General information			
Product type designation	server modules for BaseCarrier		
HW functional status	from FS01		
Input current			
Current consumption, max.	30 mA		
Ambient conditions			
Ambient temperature during operation			
• min.	No condensation		
• horizontal installation, min.	-30 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-30 °C		
• vertical installation, max.	50 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual		
Dimensions			
Width	15 mm		
Height	73 mm		
Depth	58 mm		
Weights			
Weight, approx.	25 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	10	EC002584
	ETIM	9	EC002584
	ETIM	8	EC002584
	ETIM	7	EC002584
Approvals / Certificates			
General Product Approval			For use in hazardous locations

[Manufacturer Declaration](#)



For use in hazardous locations

[CCC-Ex](#)

[FM](#)



[Type Examination Certificate](#)

[Miscellaneous](#)



last modified:

7/2/2025