

# Product datasheet

Specifications



## TeSys F contactor - 4P (4 NO) - AC-1 - $\leq 440$ V 275 A - coil 400 V AC

LC1F1854V7

⚠ Discontinued on: 11 Jan 2023

⚠ Discontinued

### Main

|                                |   |
|--------------------------------|---|
| Range                          | TeSys                                       |
| Range of product               | TeSys F                                     |
| Product or component type      | Contactor                                   |
| Device short name              | LC1F  |
| Contactor application          | Resistive load                              |
| Utilisation category           | AC-1  |
| Poles description              | 4P  |
| [Ue] rated operational voltage | $\leq 460$ V DC<br>$\leq 690$ V AC 50/60 Hz |
| [Uc] control circuit voltage   | 400 V AC 40...400 Hz                        |
| [Ie] rated operational current | 275 A (at $<40$ °C) at $\leq 440$ V AC-1    |

### Complementary

|   |   |
|---|---|
| [Uimp] rated impulse withstand voltage      | 8 kV  |
| [Ith] conventional free air thermal current | 275 A (at 40 °C)  |
| Rated breaking capacity                     | 1480 A conforming to IEC 60947-4-1  |
| [Icw] rated short-time withstand current    | 1500 A 40 °C - 10 s<br>920 A 40 °C - 30 s<br>740 A 40 °C - 1 min<br>500 A 40 °C - 3 min<br>400 A 40 °C - 10 min             |
| Associated fuse rating                      | 200 aM at $\leq 440$ V<br>315 aG at $\leq 440$ V  |
| Average impedance                           | 0.33 mOhm - Ith 275 A 50 Hz   |
| [Ui] rated insulation voltage               | 1000 V conforming to IEC 60947-4-1<br>1500 V conforming to VDE 0110 group C   |
| Power dissipation per pole                  | 12 W AC-3<br>25 W AC-1  |
| Overvoltage category                        | III   |
| power pole contact composition              | 4 NO  |
| Control circuit voltage limits              | Operational: 0.85...1.1 U <sub>c</sub> 40...400 Hz (at 55 °C)<br>Drop-out: 0.2...0.55 U <sub>c</sub> 40...400 Hz (at 55 °C) |
| Mechanical durability                       | 10 Mcycles  |
| Inrush power in VA                          | 1070 VA, 40...400 Hz cos phi 0.9 (at 20 °C)   |
| Hold-in power consumption in VA             | 9.9 VA, 40...400 Hz cos phi 0.9 (at 20 °C)  |

|                                |   |
|--------------------------------|---|
| <b>Maximum operating rate</b>  | 2400 cyc/h 55 °C  |
| <b>Operating time</b>          | 35 ms closing (at U <sub>c</sub> )<br>130 ms opening (at U <sub>c</sub> )   |
| <b>Connections - terminals</b> | Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible without cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> flexible with cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> flexible with cable end<br>Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> solid without cable end<br>Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> solid without cable end<br>Power circuit: bar 2 cable(s) - busbar cross section: 25 x 3 mm<br>Power circuit: lugs-ring terminals 1 cable(s) 150 mm <sup>2</sup><br>Power circuit: connector 1 cable(s) 150 mm <sup>2</sup><br>Power circuit: bolted connection |
| <b>Tightening torque</b>       | Control circuit: 1.2 N.m<br>Power circuit: 18 N.m   |
| <b>Mounting support</b>        | Plate   |
| <b>Heat dissipation</b>        | 8...9.8 W   |
| <b>Standards</b>               | JIS C8201-4-1<br>IEC 60947-1<br>EN 60947-4-1<br>IEC 60947-4-1<br>EN 60947-1   |
| <b>Product certifications</b>  | DNV<br>RMRoS<br>UL<br>LROS (Lloyds register of shipping)<br>BV<br>CCC<br>ABS<br>RINA<br>CB  |
| <b>Compatibility code</b>      | LC1F  |
| <b>Control circuit type</b>    | AC at 40...400 Hz   |

## Environment

|  |   |
|--|---|
| <b>IP degree of protection</b>                               | IP2X front face with shrouds conforming to IEC 60529<br>IP2X front face with shrouds conforming to VDE 0106 |
| <b>Protective treatment</b>                                  | TH  |
| <b>Ambient air temperature for operation</b>                 | -5...55 °C  |
| <b>Ambient air temperature for storage</b>                   | -60...80 °C   |
| <b>Permissible ambient air temperature around the device</b> | -40...70 °C   |
| <b>Height</b>  | 174 mm  |
| <b>Width</b>   | 208.5 mm  |
| <b>Depth</b>   | 181 mm  |
| <b>Operating altitude</b>                                    | 3000 m without derating   |
| <b>Net weight</b>  | 5.45 kg   |

## Packing Units

|                                     |         |
|-------------------------------------|---------|
| <b>Unit Type of Package 1</b>       | PCE     |
| <b>Number of Units in Package 1</b> | 1       |
| <b>Package 1 Height</b>             | 21.5 cm |
| <b>Package 1 Width</b>              | 19.5 cm |
| <b>Package 1 Length</b>             | 26 cm   |

---

|                  |          |
|------------------|----------|
| Package 1 Weight | 5.981 kg |
|------------------|----------|

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

PVC free

Yes

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins