

Product datasheet

Specifications



contactor TeSys Deca - 4 poles (2NO + 2NC) - AC-1 440V 60 A - coil 12 V DC

LP1D40008JW

⚠ Discontinued on: 14 Nov 2017

⚠ Discontinued

Main

Range	TeSys
Range of product	TeSys D
Product or component type	Contacteur
Device short name	LP1D
Contacteur application	Resistive load
Utilisation category	AC-1
Poles description	4P
[Ue] rated operational voltage	Power circuit: <= 690 V AC 25...400 Hz
[Ie] rated operational current	60 A (at <60 °C) at <= 440 V AC AC-1 for power circuit
[Uc] control circuit voltage	12 V DC

Complementary

Motor power kW	18.5 kW at 380...400 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 30 kW at 660...690 V AC 50/60 Hz 22 kW at 415...440 V AC 50/60 Hz 11 kW at 220...230 V AC 50/60 Hz
Motor power hp	10 hp at 200/208 V AC 60 Hz for 3 phases motors conforming to CSA 10 hp at 200/208 V AC 60 Hz for 3 phases motors conforming to UL 10 hp at 230/240 V AC 60 Hz for 3 phases motors conforming to CSA 10 hp at 230/240 V AC 60 Hz for 3 phases motors conforming to UL 3 hp at 115 V AC 60 Hz for 1 phase motors conforming to CSA 3 hp at 115 V AC 60 Hz for 1 phase motors conforming to UL 30 hp at 460/480 V AC 60 Hz for 3 phases motors conforming to CSA 30 hp at 460/480 V AC 60 Hz for 3 phases motors conforming to UL 30 hp at 575/600 V AC 60 Hz for 3 phases motors conforming to CSA 30 hp at 575/600 V AC 60 Hz for 3 phases motors conforming to UL 5 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA 5 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL
Compatibility code	LP1D
Pole contact composition	2 NO + 2 NC
Protective cover	With
[Ith] conventional free air thermal current	10 A (at 60 °C) for control circuit 60 A (at 60 °C) for power circuit
Irms rated making capacity	800 A at 440 V for power circuit conforming to IEC 60947 250 A AC for control circuit conforming to IEC 60947-5-1
Rated breaking capacity	800 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for control circuit conforming to IEC 60947-5-1 80 A gG at <= 690 V coordination type 1 for power circuit 80 A gG at <= 690 V coordination type 2 for power circuit

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Average impedance	1.5 mOhm - lth 60 A 50 Hz for power circuit
Power dissipation per pole	5.4 W AC-1
[Ui] rated insulation voltage	Control circuit: 600 V CSA certified Control circuit: 600 V UL certified Power circuit: 600 V CSA certified Power circuit: 600 V UL certified Control circuit: 690 V conforming to IEC 60947-1 Power circuit: 690 V conforming to IEC 60947-1
Overvoltage category	III
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947
Mechanical durability	10000000 cycles
Control circuit type	DC wide range
Coil technology	Built-in bidirectional peak limiting diode suppressor
Control circuit voltage limits	0.1...0.3 Uc (60 °C):drop-out 0.75...1.25 Uc (60 °C):operational
Inrush power in W	19 W (at 20 °C)
Hold-in power consumption in W	7.4 W at 20 °C
Operating time	20 ms opening 50 ms closing
Time constant	34 ms
Maximum operating rate	3600 cyc/h 60 °C
Connections - terminals	Control circuit: screw clamp terminal 1 1...4 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminal 2 1...4 mm ² - cable stiffness: solid without cable end Control circuit: screw clamp terminal 1 1...2.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 2 1...2.5 mm ² - cable stiffness: flexible without cable end Control circuit: screw clamp terminal 1 1...4 mm ² - cable stiffness: flexible with cable end Control circuit: screw clamp terminal 2 1...4 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminal 1 2.5...35 mm ² - cable stiffness: solid with cable end Power circuit: screw clamp terminal 2 2.5...35 mm ² - cable stiffness: solid with cable end Power circuit: screw clamp terminal 1 2.5...35 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminal 2 2.5...25 mm ² - cable stiffness: flexible without cable end Power circuit: screw clamp terminal 1 2.5...35 mm ² - cable stiffness: flexible with cable end Power circuit: screw clamp terminal 2 2.5...35 mm ² - cable stiffness: flexible with cable end
Tightening torque	Control circuit: 1.2 N.m - on screw clamp terminal - with screwdriver flat Ø 6 mm Control circuit: 1.2 N.m - on screw clamp terminal - with screwdriver Philips No 2 Power circuit: 5 N.m - on screw clamp terminal - with screwdriver flat Ø 6 to Ø 8 mm hexagonal screw head
Auxiliary contacts type	type mirror contact 1 NC conforming to IEC 60947-4-1 type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
Minimum switching voltage	17 V for control circuit
Minimum switching current	5 mA for control circuit
Insulation resistance	> 10 MOhm for control circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contacts 1.5 ms on energisation between NC and NO contacts
Mounting support	Plate Rail

Environment

Standards	VDE 0660 NF C 63-110 IEC 60947-1 IEC 60947-4-1 EN 60947-1 BS 5424 EN 60947-4-1 JEM 1038
Product certifications	RINA Sichere trennung CSA UL GL DNV SNCF GOST PTB
IP degree of protection	IP2X conforming to IEC 60529 IP2X conforming to VDE 0106
Climatic withstand	conforming to IACS E10 exposure to damp heat
Permissible ambient air temperature around the device	-60...80 °C storage -40...60 °C operation 60...70 °C with derating
Operating altitude	3000 m without derating
Fire resistance	850 °C conforming to IEC 60695-2-1
Flame retardance	V1 conforming to UL 94
Mechanical robustness	Shocks contactor opened (10 Gn) Shocks contactor closed (15 gn) Vibrations contactor opened (2 Gn, 5...300 Hz) Vibrations contactor closed (4 Gn, 5...300 Hz)
Height	127 mm
Width	85 mm
Depth	182 mm
Product weight	2.21 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins