

Product datasheet

Specifications



busbar EasyPact - 400 A - 10 ways

EZB400W10

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

| | |
|---------------------------|---------------------------------------|
| Range of product | EasyPact |
| Range | EasyPact |
| Device short name | busbar |
| Product or component type | Busbar |
| Device application | Connection |
| Range compatibility | EasyPact EasyPact EZB circuit breaker |
| [In] rated current | 400 A |
| Number of ways | 10 ways |

Complementary

| | |
|--|-------------------------------|
| [Ui] rated insulation voltage | 690 V AC 50/60 Hz |
| [Ue] rated operational voltage | 550 V AC 50/60 Hz |
| Number of devices | 10 (3P) 14 (2P) 30 (1P) |
| Busbar extension | 2 or 4 ways |
| [Icw] rated short-time withstand current | 40 kA for 1 s |
| Height | 515 mm |
| Width | 416 mm |
| Depth | 107 mm |

Environment

| | |
|-----------|-----------|
| Standards | IEC 60439 |
|-----------|-----------|

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins