

# Product datasheet

Specifications



## cable for pulse/direction signal, Lexium SD3, 5V, 0.5m

VW3S8208R05

⚠ Discontinued on: 31 Mar 2023

⚠ To be end-of-service on: 31 Mar 2028

⚠ To be discontinued

## Main

Accessory / separate part designation	Cable for pulse/direction signal
Accessory / separate part type	Connecting cable
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Between stepper drive SD326 and motion controller TLM2
Range compatibility	Lexium SD3
Cable length	0.5 m

## Complementary

Product compatibility	SD326
[Uc] control circuit voltage	5 V
Electrical connection	1 connector 24-pole Molex (SD326) 1 connector SUB-D 15 (TLM2)

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	26 cm
Package 1 Length	29 cm
Package 1 Weight	90 g
Unit Type of Package 2	S04
Number of Units in Package 2	60
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	6.652 kg
Unit Type of Package 3	S04
Number of Units in Package 3	60
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm

---

Package 3 Weight	6.652 kg
------------------	----------

## Contractual warranty

---

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

Take-back

Yes