

# Product datasheet

Specifications

## Motors



AC servo motor BDH - 2 N.m - 8000 rpm - untapped shaft - without brake - IP67

BDH0702C25A2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118172159

## Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	2 N.m for LXM15LU60N4 3 phases
Peak stall torque	5.74 N.m for LXM15LU60N4 at 230 V 3 phases 5.74 N.m for LXM15LU60N4 at 400 V 3 phases 5.74 N.m for LXM15LU60N4 at 480 V 3 phases
Nominal output power	250 W for LXM15LU60N4 at 230 V 3 phases 500 W for LXM15LU60N4 at 400 V 3 phases 600 W for LXM15LU60N4 at 480 V 3 phases
Nominal torque	1.64 N.m for LXM15LU60N4 at 480 V 3 phases 1.7 N.m for LXM15LU60N4 at 400 V 3 phases 1.85 N.m for LXM15LU60N4 at 230 V 3 phases
Nominal speed	1500 rpm for LXM15LU60N4 at 230 V 3 phases 3000 rpm for LXM15LU60N4 at 400 V 3 phases 3500 rpm for LXM15LU60N4 at 480 V 3 phases
Maximum mechanical speed	8000 rpm
Product compatibility	LXM15LU60N4 at 230 V 3 phases LXM15LU60N4 at 400 V 3 phases LXM15LU60N4 at 480 V 3 phases
Shaft end	Untapped
IP degree of protection	IP67
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	Without
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	8

## Complementary

Range compatibility	Lexium 15
Maximum current Irms	4.03 A
Torque constant	1.4 N.m/A at 120 °C
Back emf constant	89.8 V/krpm at 120 °C
Stator resistance	23 Ohm at 20 °C
Stator inductance	46.5 mH at 20 °C

---

<b>Stator electrical time constant</b>	2.02 ms at 20 °C
--	------------------

---

<b>Maximum radial force Fr</b>	150 N at 6000 rpm 165 N at 5000 rpm 180 N at 4000 rpm 200 N at 3000 rpm 240 N at 2000 rpm 300 N at 1000 rpm
--------------------------------	--

---

<b>Maximum axial force Fa</b>	0.3 x Fr
-------------------------------	----------

---

<b>Net weight</b>	2.23 kg
-------------------	---------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No