

Product datasheet

Specifications



Blown fuse indicator - 4P (only for NFC type) -1NO+1NC- for Fupact INFC125

LV480449

⚠ Discontinued on: 23 Jan 2021

⚠ Discontinued

Main

Range of product	INF100...160
Range	FuPact
Device short name	blown fuse indicator
Product or component type	Blown Fuse Indicator
Device application	Display
Range compatibility	FuPact Fupact INF fuse-switch disconnecter
Poles description	4P
Signal contacts composition	1 NO + 1 NC

Complementary

[I _{th}] conventional free air thermal current	16 A
[I _e] rated operational current	AC-15: 6 A at 24 V AC 50/60 Hz DC-12: 2 A at 48 V DC DC-12: 6 A at 24 V DC AC-15: 2 A at 660/690 V AC 50/60 Hz AC-15: 3 A at 440 V AC 50/60 Hz AC-15: 4 A at 380/415 V AC 50/60 Hz AC-15: 6 A at 110 V AC 50/60 Hz AC-15: 6 A at 220/240 V AC 50/60 Hz AC-15: 6 A at 250 V AC 50/60 Hz AC-15: 6 A at 48 V AC 50/60 Hz DC-12: 0.1 A at 380/415 V DC DC-12: 0.1 A at 440 V DC DC-12: 0.4 A at 220/240 V DC DC-12: 0.4 A at 250 V DC DC-12: 1.1 A at 110 V DC
Minimum load	10 mA at 24 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1 cm
Package 1 Width	10 cm
Package 1 Length	17 cm
Package 1 Weight	35 g

Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

[EU RoHS Directive](#)

Compliant

PVC free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins