

General Duty Safety Switches

Selection



4 SAFETY SWITCHES

System	Ampere Rating	Indoor — Type 1		Outdoor — Type 3R		Horsepower Ratings ^①						
		Catalog Number	7 (lbs.) Std. Pkg.	Catalog Number	Ship. Wt. (lbs.) Std. Pkg.	240V AC			250 Volt DC			
						1-Phase, 2-Wire	2-Phase, 4-Wire	3-Phase, 3-Wire				
Std.	Max.	Std.	Max.	Std.	Max.	Std.						

240 Volt Fusible

2-Pole, 2-Fuse, and Solid Neutral^{②③④}

240 Volt AC/250 Volt DC

Ampere Rating	Catalog Number	Std. Pkg.	Ship. Wt. (lbs.) Std. Pkg.	1-Phase, 2-Wire		2-Phase, 4-Wire		3-Phase, 3-Wire		250 Volt DC
				Std.	Max.	Std.	Max.	Std.	Max.	
30	GF221N	35 ^②	35 ^②	1½	3	—	—	3	7½	5
60	GF222N	14	14	3	10	—	—	7½	15	10
100	GF223N	23	24	7½	15	—	—	15	30	20
200	GF224N	47	48	15	—	—	—	25	60	40
400	GF225NH ^⑤	128	130	15	—	—	—	50	125	50
400	GF225N	153	157	15	—	—	—	50	125	50
600	GF226NH ^⑤	133	135	15	—	—	—	75	200	—
600	GF226N	159	159	15	—	—	—	75	200	—

3-Pole, 3-Fuse, and Solid Neutral^④

240 Volt AC/250 Volt DC

Ampere Rating	Catalog Number	Std. Pkg.	Ship. Wt. (lbs.) Std. Pkg.	1-Phase, 2-Wire		2-Phase, 4-Wire		3-Phase, 3-Wire		250 Volt DC
				Std.	Max.	Std.	Max.	Std.	Max.	
30	GF321N	24 ^④	24 ^④	1½	3	—	—	3	7½	5
60	GF322N	15	15	3	10	—	—	7½	15	10
100	GF323N	25	25	7½	15	—	—	15	30	20
200	GF324N	49	50	15	—	—	—	25	60	40
400	GF325NH ^⑤	136	138	15	—	—	—	50	125	50
400	GF325N	158	162	15	—	—	—	50	125	50
600	GF326NH ^⑤	138	141	15	—	—	—	75	200	—
600	GF326N	161	165	15	—	—	—	75	200	—

240 Volt Non-Fusible^{③④}

2-Pole or 3-Pole

240 Volt AC/250 Volt DC

Ampere Rating	Catalog Number	Std. Pkg.	Ship. Wt. (lbs.) Std. Pkg.	1-Phase, 2-Wire		2-Phase, 4-Wire		3-Phase, 3-Wire		250 Volt DC
				Std.	Max.	Std.	Max.	Std.	Max.	
30	GNF321	24 ^④	24 ^④	—	3	—	—	7½	—	5
60	GNF322	12	13	—	10	—	—	15	—	10
100	GNF323	23	24	—	15	—	—	30	—	20
200	GNF324	46	47	—	15	—	—	60	—	40
400	GNF325	114	Use 600V Switch — HNF365R	—	15	—	—	125	—	50
600	GNF326	116	Use 600V Switch — HNF366R	—	15	—	—	200	—	—

① Dual horsepower ratings: Std.- applies when non-time delay fuses are installed. Max.- applies when time-delay fuses are installed.

② These switches are UL-listed for application on grounded B-phase systems.

③ Suitable for use on 3-phase motor loads.

④ Service entrance labeled.

⑤ Has provision for ECHA type hub.

⑥ 5 switches per standard package.

⑦ 10 switches per standard package.

⑧ Height reduced switch (45.25 rather than 56 inches in height) for use with 500MCM or smaller conductors.