

Product datasheet

Specifications



circuit breaker EasyPact Ezc400H - TMD - 350 A - 4 poles 3d

Ezc400H4350

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

Main

| | |
|---|--|
| Range of product | EasyPact |
| Product or component type | Circuit breaker |
| Device short name | EasyPact Ezc400H |
| Circuit breaker name | EasyPact Ezc400H |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [In] rated current | 400 A at 40 °C |
| [U _i] rated insulation voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [U _{imp}] rated impulse withstand voltage | 8 kV conforming to IEC 60947-2 |
| [U _e] rated operational voltage | 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity code | H |
| Breaking capacity | 50 kA Icu at 380 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 400...415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 |
| [I _{cs}] rated service breaking capacity | 25 kA at 380 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 220/230 V AC 50/60 Hz conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit rating | 350 A at 50 °C |
| Protection type | Overload protection Short-circuit protection |
| Pollution degree | 3 conforming to IEC 60947 |

Complementary

| | |
|---------------|--------|
| Control type | Toggle |
| Mounting mode | Fixed |

| | |
|-----------------------------------|---|
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Mechanical durability | 10000 cycles |
| Electrical durability | Category A: 4000 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2 |
| Connection pitch | 44 mm |
| Local signalling | Positive contact indication |
| Neutral protection setting | Without protection |
| Earth-leakage protection | Without |
| Height | 255 mm |
| Width | 185 mm |
| Depth | 140 mm |

Environment

| | |
|--|---|
| Standards | EN/IEC 60947-2 EN/IEC 60947-1 JIS C8201-2-2 GB/T 14048.2 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -35...85 °C |

Packing Units

| | |
|-------------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 18 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

