

! If you have questions regarding login with Siemens ID, please check the [FAQ](#).

SiePortal

The integrated platform for your informatio workflow – bringing together Industry Mall

SiePortal | Region and language | Contact | Help | Support Request

Search for products

> Home > Catalogue > ... > ... > Pressure transmitters > Single-range transmitters > SITRANS P200 > 7MF1565-5CB00-1AA1

Products & Services Support

7MF1565-5CB00-1AA1



Image similar

SITRANS P200 Transmitters for pressure and absolute pressure for general applications Non-linearity: 0,25 percent (typically) wetted parts material:ceramics, stainless steel plus sealing material; non-wetted parts material: stainless steel Measuring range for absolute: 0 to 16 bar abs., Overload- pressure 40 bar abs. Output signal: 4 to 20 mA two-wire connection, power supply DC 7 to 33 V without explosion protection Electrical connection: plug to DIN EN 175301-803-A, thread for packed gland M16 (with connector) Process connection: G1/2" male to EN 837-1 (1/2" BSP male) (standard for metric pressure ranges mbar, bar) Sealing material between sensor and housing: Viton (FPM, Standard) Standard version

List Price	Show prices
Customer Price	Show prices
Additional Services	For this product we can offer Services like Spare Part Delivery/Repair/Exchange. You have currently no rights to enter the Service Web Shop for that. For further information & to order this service, please contact your local Spares&Repair Partner
	For this product we can offer extended warranty contracts EEO (material exchange for a single product) OEM RSC (Repair Service Contract for a whole machine) For further information & to order these services, please contact your local Siemens Service Partner
Service & Support (Manuals, Certificates, FAQs...)	Download

Product

Article Number (Market Facing Number)	7MF1565-5CB00-1AA1
Product Description	SITRANS P200 Transmitters for pressure and absolute pressure for general applications Non-linearity: 0,25 percent (typically) wetted parts material:ceramics, stainless steel plus sealing material; non-wetted parts material: stainless steel Measuring range for absolute: 0 to 16 bar abs., Overload- pressure 40 bar abs. Output signal: 4 to 20 mA two-wire connection, power supply DC 7 to 33 V without explosion protection Electrical connection: plug to DIN EN 175301-803-A, thread for packed gland M16 (with connector) Process connection: G1/2" male to EN 837-1 (1/2" BSP male) (standard for metric pressure ranges mbar, bar) Sealing material between sensor and housing: Viton (FPM, Standard) Standard version
Product family	SITRANS P200
Product Lifecycle (PLM)	PM300:Active Product

Price data

Price Group / Headquarter Price Group	8P4
List Price	Show prices
Customer Price	Show prices
Metal Factor	None

Delivery information

Export Control Regulations	ECCN : EAR99H / AL : 91999IR
Estimated dispatch time (Working Days)	1 Day/Days
Net Weight (kg)	0.200 Kg
Packaging Dimension	85.00 x 157.00 x 41.00
Package size unit of measure	MM
Quantity Unit	1 Piece
Packaging Quantity	1

Additional Product Information

EAN	4047623602736
UPC	Not available
Commodity Code	90262020
LKZ_FDB/ CatalogID	F101-1
Product Group	4778
Group Code	R3P0
Country of origin	Switzerland
Compliance with the substance restrictions according to RoHS directive	not available
Product class	A: Standard product which is a stock item could be returned within the returns guidelines/period.
WEEE (2012/19/EU) Take-Back Obligation	Yes
REACH Art. 33 Duty to inform according to the current list of candidates	Yes
SCIP number	Not available

Classifications

Version Classification

eClass	12	27-20-06-14
eClass	14	27-20-06-14
eClass	6	27-20-06-14
eClass	7.1	27-20-06-14
eClass	8	27-20-06-14
eClass	9	27-20-06-14
eClass	9.1	27-20-06-14
ETIM	7	EC002990
ETIM	8	EC002990
ETIM	9	EC002990
UNSPSC	15	32-15-17-03

;