

Product datasheet

Specifications



circuit breaker EasyPact EZC400H - TMD - 350 A - 4 poles 3d

EZC400H4350N

⚠ Discontinued on: 1 Dec 2024

⚠ To be discontinued

Main

| | |
|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product | EasyPact |
| Product or component type | Circuit breaker |
| Device short name | EasyPact EZC400H |
| Circuit breaker name | EasyPact EZC400H |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 3t |
| Network type | AC |
| Network frequency | 50/60 Hz |
| [In] rated current | 400 A at 40 °C |
| [Ui] rated insulation voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 60947-2 |
| [Ue] rated operational voltage | 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| Breaking capacity code | H |
| Breaking capacity | 50 kA Icu at 380 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 400...415 V AC 50/60 Hz conforming to IEC 60947-2 50 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 70 kA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ics] rated service breaking capacity | 25 kA at 380 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 25 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 35 kA at 220/230 V AC 50/60 Hz conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Trip unit rating | 350 A at 50 °C |
| Protection type | Short-circuit protection Overload protection |
| Pollution degree | 3 conforming to IEC 60947 |

Complementary

| | |
|---------------|--------|
| Control type | Toggle |
| Mounting mode | Fixed |

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.

| | |
|---------------------------------------------|---------------------------------------------------------------------|
| Mounting support | Backplate |
| Upside connection | Front |
| Downside connection | Front |
| Mechanical durability | 10000 cycles |
| Electrical durability | Category A: 4000 cycles 415 V AC 50/60 Hz conforming to IEC 60947-2 |
| Connection pitch | 45 mm |
| Local signalling | Positive contact indication |
| Contact position indicator | Yes |
| Magnetic tripping current | 6000 A |
| Neutral protection setting | Without protection |
| Long time pick-up adjustment type Ir | Fixed |
| Long time delay adjustment type | Fixed |
| Earth-leakage protection | Without |
| Height | 255 mm |
| Width | 185 mm |
| Depth | 140 mm |
| Net weight | 6.4 kg |
| Quantity per set | 1 piece |
| Colour | Black |

Environment

| | |
|----------------------------------------------|-------------------------------------------------------------------|
| Standards | GB/T 14048.2 EN/IEC 60947-1 EN/IEC 60947-2 JIS C8201-2-2 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to EN 50102 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -35...85 °C |

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15.0 cm |
| Package 1 Width | 20.0 cm |
| Package 1 Length | 30.0 cm |
| Package 1 Weight | 7.73 kg |
| Unit Type of Package 2 | S04 |
| Number of Units in Package 2 | 3 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 40.0 cm |
| Package 2 Length | 60.0 cm |

| | |
|------------------|-----------|
| Package 2 Weight | 23.956 kg |
|------------------|-----------|

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint | 1 110 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 51 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 2 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.8 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 1 047 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 9 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards |
| SCIP Number | 2958c627-310e-4ae4-a905-31a369b1aaa8 |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| PVC free | Yes |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|


Use Again



Repack and remanufacture


| | |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in % | 43 |
| End of life manual availability | End of Life Information |
| Take-back | Nej |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Dimensions Drawings



| A | A1 | B | B1 | B2 | F1 | F2 | F3 |
|-------|-----|----|-----|-----|----|------|----|
| 127.5 | 255 | 70 | 140 | 185 | 45 | 22.5 | 90 |

Assembly



| A | A1 | B | B1 | B2 | F1 | F2 | F3 |
|-------|-----|----|-----|-----|----|------|----|
| 127.5 | 255 | 70 | 140 | 185 | 45 | 22.5 | 90 |

Performance Curves



Offer Marketing Illustration

Product benefits / Features



**EasyPact EZC
Range Accessories**

Control Accessories

- Direct rotary handle
- Extended rotary handle

Electrical Auxiliaries

- Indication contact
- Voltage releases

Connection Accessories

- Terminal extension
- Cable connectors
- Rear connectors

Insulation Accessories

- Terminal shield
- Interphase barriers

Plug-in Accessories

- [Four plug-in accessories]

Offer Marketing Illustration

Product benefits / Features

EasyPact EZC

Technical Benefits



- ideal for simple applications in smaller buildings
- Rated current from 15 to 630 A
- Breaking capacity up to 50 kA at 400/415 V.
- 1, 2, 3 and 4 pole versions and 3 frame sizes.
- Thermal-magnetic for the entire range.
- Built-in integrated earth-leakage protection (EZC 250 ELCB).
- Compliance with international standards: IEC 60947-1 and 2, CCC, EAC and other local certifications.

Offer Marketing Illustration

Product benefits / Features

EasyPact EZC Moulded Case Circuit Breaker



A photograph of a Schneider EasyPact EZC Moulded Case Circuit Breaker. It is a grey, rectangular unit with a central handle and several terminals on top and bottom. The Schneider logo is visible on the front panel.

Easy to choose
A wide range of auxiliaries, and accessories for effortless selection and complete customization.

Effortless setup
Fixed front mounting, plug-in option, front connections, and interchangeable MCCB and ELCB for seamless adaptability.

Easy to use
Positive contact indication for enhanced safety and reliability with compact case optimized for tight spaces.