

# Product data sheet

Specifications



## ASCO 4000 SERIES Power Transfer Switch

ASCOLVATS4000

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

### Main

Product Type	Automatic transfer switch
Intended Application	Industrial Application

### Complementary

Current Rating	30...4000 A
Number of Phases	Single phase Three phase
Number of Poles	2P 3P 4P
Rated Voltage	208...600 V AC 50/60 Hz
Neutral Configurations	Solid neutral Switched neutral
Open or Closed Transfer Mode	Open Closed
Manual or Delayed Transfer Mode	Delayed
Transfer Speed	< 100 ms
Controller Group	5
Communication Network Type	RS485 Ethernet Modbus
Ambient Air Temperature for Operation	23...104 °F (-5...40 °C)
Operating Altitude	> 6561.68 ft (2000 m)
Service Entrance Rated	No
Bypass Isolation Functionality	No
Operating Mode	AUTO
Provided Equipment	LED status indicator front panel
Display Type	Monochrome
Device Composition	Mechanical interlock
User Interface	Base controller with integrated LCD display

### Environmental

NEMA Degree of Protection	NEMA 3R/4X/12
Max Humidity Rating at 40 C	50 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Standards</b>	UL 1008 IEC 60947-6-1 CE
------------------	--------------------------------

## **Contractual warranty**

---

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

### Use Longer



#### Lifetime extension

Repair

No

Image of product / Alternate images

Alternative

---

