



Catalog No. TH3364R

Description: 200A 3P HD N3R 600V FUSIBLE

UPC No 783164009149

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. TH3364R



Representative Image

Descriptors

| | |
|-------------|------------|
| Category | Heavy Duty |
| GO Schedule | S1 |

Specifications

| | |
|---------------------------|-------------------|
| Voltage | 600 AC |
| Amperage | 200 A |
| Poles | 3 |
| Wires | 3 |
| Fusing | Fusible |
| Enclosure | NEMA 3R (Outdoor) |
| Options | None |
| Wire Range (Cu/Al) | 2-250 |
| 480 Vac, NEC Std, 1-ph | 25.0 hp |
| 480 Vac, NEC Std, 3-ph | 50.0 hp |
| 480 Vac, Time Delay, 1-ph | 50.0 hp |
| 480 Vac, Time Delay, 3-ph | 125.0 hp |
| 600 Vac, NEC Std, 1-ph | 30.0 hp |
| 600 Vac, NEC Std, 3-ph | 60.0 hp |
| 600 Vac, Time Delay, 1-ph | 50.0 hp |
| 600 Vac, Time Delay, 3-ph | 150.0 hp |
| 250 Vdc | 40.0 hp |
| GSA Compliance | Yes |

Classifications

| | |
|------------|-----|
| cUL Listed | Yes |
| UL Listed | Yes |

Dimensions

| | |
|--------|---------|
| Height | 31.7 in |
| Depth | 5.4 in |

by ABB

Dimensions

| | |
|--------|---------|
| Width | 13.4 in |
| Weight | 33.0 lb |