

Product datasheet

Specifications



Profibus DP communication card, Altivar, 1.5Mbps, 9 way female SUB D connector

VW3A3E307

⚠ Discontinued on: 9 Apr 2024

⚠ End-of-service on: 8 May 2024

⚠ Discontinued

Main

Product or component type	Communication card
Range compatibility	Altivar 71 Plus Altivar 61 Plus
Communication port protocol	Profibus DP
Connector type	9-way female SUB-D connector
Transmission rate	500 kbps 12 Mbps 1.5 Mbps 93.75 kbps 187.5 kbps 3 Mbps 9600 bps 19.2 kbps 6 Mbps

Complementary

Number of addresses	1...126
Communication service	CiA 402 profile I/O profile I/O data Communication monitoring can be inhibited, adjustable PPO type 5
Display type	1 LED for DX (data exchange) 1 LED for ST (status) Graphic display terminal for control word received Graphic display terminal for I/O data Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	17.1 cm
Package 1 Length	23.0 cm
Package 1 Weight	304.0 g

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No