



Control and signaling units

Harmony XB5, plastic


Flush mounted illuminated selector switches
with standard handle, with integral LED



ZB5FK1233



ZB5FK1263C0



ZB5FK1843

Flush mounted illuminated selector switches with standard handle, with integral LED for Ø 30 mm ⁽¹⁾⁽²⁾								
Shape of head	Type of operator	Positions			Color of handle	Reference		Weight kg/lb
		Number	Type			For black bezel	For gray bezel ⁽³⁾	
Heads only ⁽⁴⁾								
 	Standard handle	2-position 90°	Stay put		White	ZB5FK1213	ZB5FK1213C0	0.030/0.066
					Green	ZB5FK1233	ZB5FK1233C0	0.030/0.066
					Red	ZB5FK1243	ZB5FK1243C0	0.030/0.066
					Orange	ZB5FK1253	ZB5FK1253C0	0.030/0.066
					Yellow	ZB5FK1283	ZB5FK1283C0	0.030/0.066
					Blue	ZB5FK1263	ZB5FK1263C0	0.030/0.066
			Spring return from right to left		White	ZB5FK1413	–	0.030/0.066
					Green	ZB5FK1433	–	0.030/0.066
					Red	ZB5FK1443	–	0.030/0.066
					Orange	ZB5FK1453	–	0.030/0.066
					Yellow	ZB5FK1483	–	0.030/0.066
					Blue	ZB5FK1463	–	0.030/0.066
		3-position ± 45°	Stay put		White	ZB5FK1313	ZB5FK1313C0	0.030/0.066
					Green	ZB5FK1333	ZB5FK1333C0	0.030/0.066
					Red	ZB5FK1343	ZB5FK1343C0	0.030/0.066
					Orange	ZB5FK1353	ZB5FK1353C0	0.030/0.066
					Yellow	ZB5FK1383	ZB5FK1383C0	0.030/0.066
					Blue	ZB5FK1363	–	0.030/0.066
			Spring return to center		White	ZB5FK1513	ZB5FK1513C0	0.030/0.066
					Green	ZB5FK1533	ZB5FK1533C0	0.030/0.066
					Red	ZB5FK1543	–	0.030/0.066
					Orange	ZB5FK1553	ZB5FK1553C0	0.030/0.066
					Yellow	ZB5FK1583	ZB5FK1583C0	0.030/0.066
					Blue	ZB5FK1563	–	0.030/0.066
Spring return from right to center		White	ZB5FK1813	–	0.030/0.066			
		Green	ZB5FK1833	ZB5FK1833C0	0.030/0.066			
		Red	ZB5FK1843	–	0.030/0.066			
		Orange	ZB5FK1853	–	0.030/0.066			
		Yellow	ZB5FK1883	–	0.030/0.066			
		Blue	ZB5FK1863	–	0.030/0.066			
Spring return from left to center		White	ZB5FK1713	–	0.030/0.066			
		Green	ZB5FK1733	–	0.030/0.066			
		Red	ZB5FK1743	–	0.030/0.066			
		Orange	ZB5FK1753	–	0.030/0.066			
		Yellow	ZB5FK1783	–	0.030/0.066			
		Blue	ZB5FK1763	–	0.030/0.066			

(1) For recommended maximum number of contacts constituting the body (fixing collar and contact) associated with the head, see [page 22](#).

(2) For use with bodies comprising a light source with integral LED only.

(3) For white color plated bezel replace C0 with C1, and for other color plated bezels using the web customization tool, see [page 5](#).

(4) To add customized markings on these references using the web customization tool, see [page 5](#).