

Product data sheet

Specifications



ASCO 5701 8-Device Gateway

ASCOCAM5701GW

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Gateway with power supply

Complementary

Functions Available
Monitor status
History
Alarm
Event Logger
Operating condition of equipment
Energy and alarm reports via email

Number of Devices 8

Voltage Rating
12 V DC
24 V DC

Communication Network Type
BACnet IP
Modbus TCP/IP

Encryption Protocol AES 128

Web/Email Interfaces
FTP/HTTP/HTTPS
SMTP V3

Number of Ethernet Ports 2

Number of USB Ports 2

Device Mounting
DIN rail
Wall mounted

Solid State Drive Capacity 128 GB

Height 3.3 in (84 mm)

Width 5.5 in (140 mm)

Depth 6.0 in (152 mm)

Product Weight 3.51 lb(US) (1.59 kg)

Environmental

Standards
UL
CE
FCC
EN/IEC 60068-2-27
EN/IEC 60068-2-64

Operating Temperature -4...140 °F (-20...60 °C)

Packing Units

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	3.3 in (8.4 cm)
Package 1 Width	5.5 in (14.0 cm)
Package 1 Length	6.0 in (15.2 cm)
Package weight(Lbs)	3.51 lb(US) (1.59 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

Use Longer



Lifetime extension

Repair

No