



circuit breaker 3VA1 IEC Frame 160 breaking capacity class H Icu=70 kA @ 415 V  
3-pole, line protection TM220, ATFM, In=160 A overload protection Ir=112 A...160  
A short-circuit protection Ii=10 x In terminal connection

| Model   |                             |
|---|-----------------------------|
| product brand name  | SENTRON                     |
| product designation   | Molded case circuit breaker |
| design of the product   | Line protection             |
| design of the overcurrent release   | TM220                       |
| protection function of the overcurrent release  | LI                          |
| number of poles   | 3                           |
| General technical data  |                             |
| insulation voltage / rated value  | 800 V                       |
| operating voltage / at DC / rated value   | 500 V                       |
| operating voltage / at AC / rated value   | 690 V                       |
| power loss [W] / maximum  | 38 W                        |
| mechanical service life (operating cycles) / typical  | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 9 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V  | 6 300                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version   | Without                     |
| product function  |                             |
| • communication function  | No                          |
| • other measurement function  | No                          |
| Net Weight  | 1.066 kg                    |
| Current   |                             |
| operational current   |                             |
| • at 40 °C  | 160 A                       |
| • at 45 °C  | 160 A                       |
| • at 50 °C  | 160 A                       |
| • at 55 °C  | 158 A                       |
| • at 60 °C  | 155 A                       |
| • at 65 °C  | 153 A                       |
| • at 70 °C  | 150 A                       |
| Switching capacity according to IEC 60947   |                             |
| switching capacity class of the circuit breaker   | H                           |
| maximum short-circuit current breaking capacity (Icu)   |                             |
| • at 240 V  | 100 kA                      |
| • at 415 V  | 70 kA                       |
| • at 440 V  | 36 kA                       |
| • at 500 V  | 10 kA                       |
| • at 690 V  | 10 kA                       |

|  |  |
|--|--|
| operating short-circuit current breaking capacity (Ics)  |  |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 100 kA<br>70 kA<br>36 kA<br>5 kA<br>5 kA   |
| short-circuit current making capacity (Icm)  |  |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 220 kA<br>154 kA<br>75.5 kA<br>17 kA<br>17 kA  |
| design of short-circuit protection   | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Adjustable parameters

|  |                    |
|--|--------------------|
| product feature / for L-tripping / can be switched on/off                                | No                 |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic |                    |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 112 A<br>160 A     |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic     |                    |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 1 s<br>1 s         |
| adjustable response value setting current (Ii) / for I-tripping                          |                    |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 1 600 A<br>1 600 A |
| adjustable setting current (InN) / for N-tripping  |                    |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>           | 0 A<br>0 A         |
| product function / grounding protection  | No                 |

#### Mechanical Design

|   |                                 |
|---|---------------------------------|
| product component   |                                 |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul> | No<br>No<br>No                  |
| height [in]   | 5.12 in                         |
| height  | 130 mm                          |
| width [in]  | 3 in                            |
| type of connectable conductor cross-sections / of the round conductor terminal / stranded                                     | 1 x (1,5 - 70 mm <sup>2</sup> ) |
| width   | 76.2 mm                         |
| depth [in]  | 2.76 in                         |
| depth   | 70 mm                           |

#### Connections

|   |                            |
|---|----------------------------|
| arrangement of electrical connectors / for main current circuit                       | Front terminal             |
| type of electrical connection / for main current circuit                              | box terminal on both sides |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)    | Silver                     |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | Tin                        |

#### Auxiliary circuit

|  |   |
|--|---|
| number of CO contacts / for auxiliary contacts | 0 |
|--|---|

#### Accessories

|  |     |
|--|-----|
| product extension / optional / motor drive | Yes |
|--|-----|

#### Environmental conditions

|  |                 |
|--|-----------------|
| protection class IP / on the front   | IP40            |
| ambient temperature  |                 |
| <ul style="list-style-type: none"> <li>• during operation / minimum</li> <li>• during operation / maximum</li> </ul> | -25 °C<br>70 °C |

- during storage / minimum -40 °C
- during storage / maximum 80 °C

#### Environmental footprint

|  |           |
|--|-----------|
| Environmental Product Declaration(EPD)                   | Yes       |
| global warming potential [CO2 eq] / total                | 190 kg    |
| global warming potential [CO2 eq] / during manufacturing | 4.67 kg   |
| global warming potential [CO2 eq] / during operation     | 186 kg    |
| global warming potential [CO2 eq] / after end of life    | -0.826 kg |
| reference code / according to IEC 81346-2                | Q         |

#### Approvals / Certificates

##### General Product Approval



[Miscellaneous](#)



[Confirmation](#)

##### General Product Approval

##### EMV

##### Test Certificates



[Miscellaneous](#)

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

#### Maritime application



[CCS \(China Classification Society\)](#)

#### other

#### Environment

[Miscellaneous](#)

[Confirmation](#)



[Environmental Confirmations](#)

[Environmental Confirmations](#)



#### Environment



#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1116-6EE36-0AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA1116-6EE36-0AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1116-6EE36-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1116-6EE36-0AA0)

##### CAX-Online-Generator

<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>

##### Characteristic curves





