

# Product datasheet

Specifications



## insulation monitoring module - for NSX400..630 - 4 poles

LV432660

⚠ Discontinued on: 22 Jun 2021

⚠ Discontinued

### Main

Product or component type	Insulation monitoring device
Device application	Insulation
Range compatibility	ComPact ComPact NSX400 ComPact ComPact NSX630
Poles description	4P

### Complementary

[Ue] rated operational voltage	200...440 V
Network type	AC
Network frequency	50/60 Hz
Measurement accuracy	-50 %...0 %
Residual earth-leakage sensitivity adjustment type	Adjustable
[Δn] residual earth-leakage sensitive adjustment	0.1 A 0.2 A 0.5 A 1 A
[Δt] residual earth-leakage time delay adjustment	5...10 s

### Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.5 cm
Package 1 Width	17 cm
Package 1 Length	20 cm
Package 1 Weight	3.288 kg

### Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

EU RoHS Directive

[Compliant](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins