

# Product datasheet

Specifications



## AC servo motor BSH - 2.12 N.m - 3000 rpm - keyed shaft - without brake - IP65

BSH0702M31A2A

! Discontinued

! Discontinued on: 18 Apr 2024

! To be end-of-service on: 18 Apr 2026

### Main

Device short name	BSH
Product or component type	Servo motor
Maximum mechanical speed	8000 rpm
Continuous stall torque	2.12 N.m for LXM15LU60N4, 400 V, three phase 2.12 N.m for LXM15LU60N4, 480 V, three phase 2.12 N.m for LXM05AD10M2, 200...240 V, single phase 2.12 N.m for LXM05AD10M3X, 200...240 V, three phase 2.12 N.m for LXM05BD10M2, 200...240 V, single phase 2.12 N.m for LXM05BD10M3X, 200...240 V, three phase 2.12 N.m for LXM05CD10M2, 200...240 V, single phase 2.12 N.m for LXM05CD10M3X, 200...240 V, three phase
Peak stall torque	5.63 N.m for LXM05AD10M2, 200...240 V, single phase 5.63 N.m for LXM05BD10M2, 200...240 V, single phase 5.63 N.m for LXM05CD10M2, 200...240 V, single phase 5.63 N.m for LXM15LU60N4, 400 V, three phase 5.63 N.m for LXM15LU60N4, 480 V, three phase 5.63 N.m for LXM05AD10M3X, 200...240 V, three phase 5.63 N.m for LXM05BD10M3X, 200...240 V, three phase 5.63 N.m for LXM05CD10M3X, 200...240 V, three phase
Nominal output power	300 W for LXM05AD10M2, 200...240 V, single phase 300 W for LXM05BD10M2, 200...240 V, single phase 300 W for LXM05CD10M2, 200...240 V, single phase 300 W for LXM05AD10M3X, 200...240 V, three phase 300 W for LXM05BD10M3X, 200...240 V, three phase 300 W for LXM05CD10M3X, 200...240 V, three phase 594 W for LXM15LU60N4, 400 V, three phase 753 W for LXM15LU60N4, 480 V, three phase
Nominal torque	2 N.m for LXM05AD10M2, 200...240 V, single phase 2 N.m for LXM05BD10M2, 200...240 V, single phase 2 N.m for LXM05CD10M2, 200...240 V, single phase 1.8 N.m for LXM15LU60N4, 480 V, three phase 1.89 N.m for LXM15LU60N4, 400 V, three phase 2 N.m for LXM05AD10M3X, 200...240 V, three phase 2 N.m for LXM05BD10M3X, 200...240 V, three phase 2 N.m for LXM05CD10M3X, 200...240 V, three phase
Nominal speed	1500 rpm for LXM05AD10M2, 200...240 V, single phase 1500 rpm for LXM05BD10M2, 200...240 V, single phase 1500 rpm for LXM05CD10M2, 200...240 V, single phase 1500 rpm for LXM05AD10M3X, 200...240 V, three phase 1500 rpm for LXM05BD10M3X, 200...240 V, three phase 1500 rpm for LXM05CD10M3X, 200...240 V, three phase 3000 rpm for LXM15LU60N4, 400 V, three phase 4000 rpm for LXM15LU60N4, 480 V, three phase

<b>Product compatibility</b>	LXM05AD10M2 at 200...240 V single phase LXM05BD10M2 at 200...240 V single phase LXM05CD10M2 at 200...240 V single phase LXM05AD10M3X at 200...240 V three phase LXM05BD10M3X at 200...240 V three phase LXM05CD10M3X at 200...240 V three phase LXM15LU60N4 at 400 V three phase LXM15LU60N4 at 480 V three phase
<b>Shaft end</b>	Keyed
<b>IP degree of protection</b>	IP65 standard IP67 with IP67 kit
<b>Speed feedback resolution</b>	131072 points/turn
<b>Holding brake</b>	Without
<b>Mounting support</b>	International standard flange
<b>Electrical connection</b>	Rotatable right-angled connectors

## Complementary

<b>Range compatibility</b>	Lexium 05 Lexium 15
<b>supply voltage max</b>	480 V
<b>Network number of phases</b>	Three phase
<b>Continuous stall current</b>	1.5 A
<b>maximum continuous power</b>	1.51 W
<b>Maximum current Irms</b>	5.9 A for LXM15LU60N4 6 A for LXM05AD10M2 6 A for LXM05AD10M3X 6 A for LXM05BD10M2 6 A for LXM05BD10M3X 6 A for LXM05CD10M2 6 A for LXM05CD10M3X
<b>Maximum permanent current</b>	6 A
<b>Switching frequency</b>	4 kHz
<b>Second shaft</b>	Without second shaft end
<b>Shaft diameter</b>	11 mm
<b>Shaft length</b>	23 mm
<b>Key width</b>	18 mm
<b>Feedback type</b>	Single turn SinCos Hiperface
<b>Motor flange size</b>	70 mm
<b>Torque constant</b>	1.46 N.m/A at 120 °C 0.87 N.m/A at 120 °C
<b>Back emf constant</b>	93 V/krpm at 120 °C 95 V/krpm at 120 °C
<b>Rotor inertia</b>	0.41 kg.cm <sup>2</sup>
<b>Stator resistance</b>	16.4 Ohm at 20 °C 17.3 Ohm at 20 °C
<b>Stator inductance</b>	74.1 mH at 20 °C 84.4 mH at 20 °C
<b>Stator electrical time constant</b>	4.52 ms at 20 °C 4.88 ms at 20 °C

<b>Maximum radial force Fr</b>	390 N at 6000 rpm 410 N at 5000 rpm 450 N at 4000 rpm 490 N at 3000 rpm 560 N at 2000 rpm 710 N at 1000 rpm
<b>Maximum axial force Fa</b>	0.2 x Fr
<b>Type of cooling</b>	Natural convection
<b>Length</b>	187 mm
<b>Centring collar diameter</b>	60 mm
<b>Centring collar depth</b>	2.5 mm
<b>Number of mounting holes</b>	4
<b>Mounting holes diameter</b>	5.5 mm
<b>Circle diameter of the mounting holes</b>	82 mm
<b>Net weight</b>	2.89 kg
<b>Sizing reference</b>	BSH0702M
<b>Network number of phases</b>	3
<b>Accuracy error [angular]</b>	1.4 °
<b>Temperature copper hot</b>	120 °C
<b>Temperature magnet hot</b>	100 °C
<b>Temperature magnet rt</b>	20 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1

## Contractual warranty

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No