

Product datasheet

Specifications



auxiliary contact, TransferPacT,
indication for OFF position, frame
800-1600A

TPSAUX72

Main

| | |
|---------------------------|--------------------------|
| Range of product | TransferPacT |
| Product or component type | Auxiliary Contact Module |
| Device application | Signalling |

Complementary

| | |
|--|--|
| Auxiliary contact composition | 2 NO + 2 NC |
| Signalling function | Switch position (off) |
| Auxiliary connection terminal | Spring 0.5...1.5 mm ² (AWG 20...AWG 16) |
| Mounting mode | Clip-on |
| [I _{th}] conventional free air thermal current | 5 A |
| Minimum load | 100 mA at 24 V DC |
| Tightening torque | 0.6 N.m +/- 0.1 N.m |
| Product compatibility | TA1A |
| Accessory / separate part category | Signalling accessory |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.700 cm |
| Package 1 Width | 10.000 cm |
| Package 1 Length | 16.000 cm |
| Package 1 Weight | 194.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 2.458 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Excluding VAT, FCA Jabal Ali & amp; are subject to change – check with your local distributor.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|---|
| Total lifecycle Carbon footprint | 3 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 2 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 0.3 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| SCIP Number | 5087b8c2-9d95-4c3d-b29e-1dae16dd345e |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |
| Halogen-free status | Halogen free plastic parts product |

Use Longer




Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------------------|---|
| Recyclability potential, in % | 64 |
| End of life manual availability | End of Life Information |
| Take-back | Nej |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |