

Product datasheet

Specifications



time delay relay for voltage release
MN - 220..240VAC 50HZ - for
NS80..NS630

29427

⚠ Discontinued

Main

Device short name	MN delay unit
Product or component type	Time delay auxiliary
Device application	Control
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NSC
[Uc] control circuit voltage	220...240 V AC 50/60 Hz 220...240 V DC

Complementary

Impulse duration	200 ms
Threshold tripping voltage	0.35...0.7 Un open 0.85 Un close
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	Fixed
Response time	< 50 ms

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins