

Product data sheet

Specifications



PowerPacT multistandard - H-Frame - 30 A - 25 KA - Therm-Mag trip unit

NHDF36030TW

Main

Range of product	PowerPact multistandard
Range	PowerPact
Product name	H-Frame
Device short name	H-Frame
Product or component type	Circuit breaker
Device application	Distribution

Complementary

Poles description	3P
Control type	Toggle
Mounting mode	Unit mount
Mounting support	DIN rail Backplate Flush
Electrical connection	Terminal nut, line side Terminal nut, load side
[In] rated current	30 A 104 °F (40 °C)
[Ui] rated insulation voltage	750 V AC 50/60 Hz IEC 60947-2
[Uimp] rated impulse withstand voltage	8 kV IEC 60947-2
[Ue] rated operational voltage	525 V AC 50/60 Hz IEC 60947-2 690 V AC 50/60 Hz IEC 947-2 600 V AC 50/60 Hz UL 489
Breaking capacity code	HD
Suitability for isolation	Yes
Utilisation category	Category A
Mechanical durability	4000 cycles
Electrical durability	4000 cycles
Connection pitch	1.8 in (45 mm)
Local signalling	ON/OFF indication
Contact position indicator	Yes
Trip unit name	TM
Trip unit technology	Thermal-magnetic
Trip unit protection functions	Basic protection
Trip unit rating	30 A

Display type	3 LEDs
Breaking capacity	Icu 25 kA 220/240 V - AC IEC 947-2 Icu 18 kA 380/415 V - AC IEC 947-2 Icu 18 kA 440/480 V - AC IEC 947-2 Icu 14 kA 500/525 V - AC IEC 947-2 25 kA 240 V - AC UL 489 18 kA 480 V - AC UL 489 14 kA 600 V - AC UL 489
[Ics] rated service breaking capacity	Ics 25 kA 220/240 V - AC IEC 947-2 Ics 18 kA 380/415 V - AC IEC 947-2 Ics 18 kA 440/480 V - AC IEC 947-2 Ics 14 kA 500/525 V - AC IEC 947-2
Long time pick-up adjustment type Ir	Fixed
Long time pick-up adjustment range	1 In
Short-time pick-up adjustment type Isd	Fixed
[Isd] short-time pick-up adjustment range	750 A
Overvoltage category	II
Provision for padlocking	Non padlockable
Height	6.4 in (163 mm)
Width	4.09 in (104 mm)
Depth	3.4 in (86 mm)
Standards	NEMA AB1 UL 489 W-C-375B/GEN IEC 60947-2 NMX J-266 CSA C22.2 No 5
Product certifications	CCC CE
Net weight	4.9 lb(US) (2.2 kg)

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Pollution degree	3 IEC 60947-1 3 IEC 60664-1
Ambient air temperature for operation	104 °F (40 °C)
Ambient air temperature for storage	-58...185 °F (-50...85 °C)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.906 in (15.000 cm)
Package 1 Width	7.480 in (19.000 cm)
Package 1 Length	8.858 in (22.500 cm)
Package 1 Weight	4.187 lb(US) (1.899 kg)
Unit Type of Package 2	S04
Number of Units in Package 2	6

Package 2 Height	11.811 in (30.000 cm)
Package 2 Width	15.748 in (40.000 cm)
Package 2 Length	23.622 in (60.000 cm)
Package 2 Weight	26.821 lb(US) (12.166 kg)

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	289 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	9 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	276 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	F6740abd-d7a0-42b0-ba51-4931bf4d8226
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
PVC free	Yes

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	45
Circularity Profile	End of Life Information
Take-back	Nej
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins