

Product datasheet

Specifications



cartridge C40-340 for surge arrester iPRD

Local distributor code:

397136739

A9L16685

⚠ Discontinued on: 3 May 2022

EAN Code: 3606480215742

⚠ Discontinued

Main

range of product	Acti9
Product or component type	Cartridge
Device short name	C40-340
Surge arrester type	Electrical distribution network
Standards	EN 61643-11 IEC 61643-1
Product certifications	OVE NF KEMA-KEUR

Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV
Earthing system	TT TN
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	15 kA
Maximum discharge current	40 kA
[Uc] maximum continuous operating voltage	340 V
Maximum [Up] voltage protection level	<1.4 kV type 2
Local signalling	Flag (white/red)
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	2
Height	50 mm
Width	18 mm
Depth	60 mm
Colour	White (RAL 9003)
Material	PBT (polybutylene terephthalate)
Response time	< 25 ns

Environment

IP degree of protection	IP20 front face:
Relative humidity	5...90 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 cm
Package 1 Width	7.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	66.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.5 cm
Package 2 Width	9.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	838.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10.543 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins