

SITRANS P DS III / P410, HART, 4-20 mA transmitter for pressure
***** Attention, product canceled / successor product
P320/P420 available! Please get in touch with your Siemens contact to determine
the successor product ***** Measuring cell filling silicone oil,
normal cleaning Span: 0,16 ... 16 bar g (2.32 ... 232 psi g), overload limit 32 bar
Diaphragm stainless steel, measuring cell stainless steel Process connection:
connection shank G1/2 B to EN 837-1 Die-cast aluminium housing Standard
design None explosion protection Electric connection and cable inlet: cable gland
M20 x 1.5 Housing cover with window (digital indicator visible, customized
adjustment supplement Y21 required) Plate inscription: english Test certificate
according to standard IEC 60770-2 Range (linear characteristic) specify in plain
text:, Y01:... to ...mBar,kpa,mpa,... Stainless steel tag plate (measuring point
description) Max.16 character, specify in plain text: Adjustment digital indicator
specify plain text Y21: mBar, bar, kpa, mpa,...

Further information

Configurable Products

Technical Data and CAx data (3d-models , eplan.macros) from configurable products cannot shown here. To display the technical data for your device configuration please open PIA LifeCyclePortal and enter there your product number (MLFB). Exemplary 3d-models and eplan-macros are available at the industry imagadatabase. Data for a specific product can be requested with help of a support request.

PIA LifeCyclePortal

<https://pia-portal.automation.siemens.com>

Industry - Image Database

<http://www.automation.siemens.com/bilddb/>

Industry Mall (Online-Order System)

<https://mall.industry.siemens.com>

Information- and Downloadcenter (Catalogs, Brochures, ...)

<http://www.siemens.com/industrial-controls/catalogs>

Support Request

<https://support.industry.siemens.com/my/us/en/requests#createRequest>

last modified:

11/25/2025 