

# Product datasheet

Specifications



## DT40 - circuit breaker - DT40N - 3P - 40A - D curve

A9N21400

⚠ Discontinued on: 10 Nov 2021

EAN Code: 3606480382031

⚠ Discontinued

### Main

Range of product	ProDis
Range	Prodis
Product name	DT40
Product or component type	Miniature circuit-breaker
Device short name	DT40N
Device application	Distribution
Poles description	3P
Number of protected poles	3
[In] rated current	40 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	D
Breaking capacity	6000 A Icn at 400 V AC 50 Hz conforming to EN/IEC 60898-1 10 kA Icu at 400...415 V AC 50 Hz conforming to IEC 60947-2
Suitability for isolation	Yes
Quality labels	NF

### Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	400 V AC 50 Hz between phases
Magnetic tripping limit	10...14 x In
[Ics] rated service breaking capacity	6000 A 100 % x Icn at 400 V AC 50 Hz conforming to EN/IEC 60898-1 7.5 kA 75 % x Icu at 400 V AC 50 Hz conforming to IEC 60947-2
Limitation class	3 conforming to EN/IEC 60898-1
[Ui] rated insulation voltage	440 V AC 50 Hz
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail

9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	78 mm
Net weight	310 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Locking options description	Padlocking device
Connections - terminals	Tunnel type terminals downstream 0.33...10 mm <sup>2</sup> flexible Tunnel type terminals downstream 0.75...16 mm <sup>2</sup> rigid Tunnel type terminals upstream 0.33...10 mm <sup>2</sup> flexible Tunnel type terminals upstream 0.75...16 mm <sup>2</sup> rigid
Wire stripping length	13 mm
Tightening torque	2 N.m
Earth-leakage protection	Separate block

## Environment

Standards	EN/IEC 60898-1 EN/IEC 60947-2
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947-2
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.3 cm
Package 1 Width	7.1 cm
Package 1 Length	9 cm
Package 1 Weight	330 g

## Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

Packaging made with recycled cardboard

Yes

SCIP Number

26ff71d1-98cf-4280-8725-455b9a6b2fb9

Halogen-free status

Halogen free product

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

End of life manual availability

No need of specific recycling operations

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins