


Product datasheet

Specifications



current transformer module,
ComPact NSX250, 250A rating, 3
poles

LV431567

⚠ Discontinued on: Mar 26, 2024 AD

⚠ Discontinued

Main

Device short name	current transformer module
Product or component type	Current transformer
Device application	Control
Range compatibility	ComPact ComPact NSX250
Poles description	3P
[In] rated current	250 A
Current transformer ratio	250/5 A
Power consumption in VA	5 VA
Accuracy class	Class 4.5

Complementary

Auxiliary connection terminal	Cable connector 2.5 mm²
-------------------------------	-------------------------

Environment

Electrical shock protection class	Class II
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK04 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	14.5 cm
Package 1 Length	17.5 cm
Package 1 Weight	1.04 kg
Unit Type of Package 2	S03
Number of Units in Package 2	4
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.647 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins