

Product datasheet

Specifications



Servo motor, Easy Lexium 18, 3kW, L130, 23 bits, OPTO INC

BCH18LM30332A6C

Main

Range compatibility	Easy Lexium 18
Device short name	BCH18
Product or component type	Servo motor

Complementary

Maximum mechanical speed	6000.0 rpm
[Us] rated supply voltage	200...240 V
Continuous stall current	18.6 A
Continuous stall torque	9.8 N.m, 220 V
Continuous power	3000 W
Peak stall torque	29.4 N.m, 220 V
Nominal output power	3000 W, 220 V
Nominal torque	9.8 N.m, 220 V
Nominal speed	3000 rpm, 220 V
Maximum permanent current	56.0 A
Shaft end	Parallel key
Shaft diameter	28 mm
Shaft length	63 mm
Key width	8 mm
Feedback type	23 bits optic incremental encoder
Holding brake	Without
Mounting support	Asian standard flange
Motor flange size	130 mm
Electrical connection	2 connectors male/female
Torque constant	0.53 N.m/A at 40 °C
Back emf constant	35.0 V/krpm at 40 °C
Number of motor poles	5.0
Rotor inertia	7.63 kg.cm²
Stator resistance	0.1 Ohm
Stator inductance	1.53 mH
Maximum radial force Fr	980 N

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum axial force Fa	392 N
Length	208.9 mm
Number of mounting holes	4.0
Circle diameter of the mounting holes	9.0 mm
Width	205.9 mm
Height	130.0 mm
Depth	208.9 mm
Net weight	10.3 kg
Encoder type	Optic encoder
Inertia	0.0 kg.cm² of brake 7.63 kg.cm² of motor

Environment

IP degree of protection	IP67
Ambient air temperature for operation	0...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	20 cm
Package 1 Length	40 cm
Package 1 Weight	11.39 kg
Unit Type of Package 2	P06
Number of Units in Package 2	18
Package 2 Height	105.0 cm
Package 2 Width	60.0 cm
Package 2 Length	80.0 cm
Package 2 Weight	205.02 kg

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	16 039 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	125 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	15 911 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins