

Product datasheet

Specifications



TeSys LE - enclosed DOL reversing starter - 9 A - 380 V AC coil

LE8K095Q7

⚠ Discontinued on: Jan 23, 2021

⚠ Discontinued

Main

| | |
|---|--|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE8K |
| Product or component type | Enclosed DOL reversing starter |
| Device application | Standard |
| Material | Polycarbonate |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay ordered separately Reversing contactor Fuse disconnecter |
| Motor power kW | 4 kW at 380/400 V AC 50/60 Hz 4 kW at 415 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz |
| [Uc] control circuit voltage | 380 V AC 50/60 Hz |
| [Ith] Conventional free air thermal current | 9 A |
| Associated fuse rating | 12 A 10 x 38 mm aM |
| Control type | Push-button stop/reset red O Push-button start down arrow Push-button start up arrow |

Complementary

| | |
|--------------------|--|
| Cable entry number | 4 2 Pg 13 + 2 Pg 16 top 4 ISO20 top 4 2 Pg 13 + 2 Pg 16 bottom 4 ISO20 bottom |
| Width | 175 mm |
| Height | 165 mm |
| Depth | 146 mm |
| Product weight | 1.6 kg |

Environment

| | |
|-------------------------|------------------------------|
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |

| | |
|---------------------------------------|----------------------|
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.5 cm |
| Package 1 Width | 17.5 cm |
| Package 1 Length | 24.5 cm |
| Package 1 Weight | 1.74 kg |

Contractual warranty

| | |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins