Product data sheet

Specifications



TeSys F - contactor coil - LX0FJ - 48 V DC low consumption

LX0FJ055

Discontinued on: Jul 12, 2021

Discontinued

Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LX0FJ
Control circuit type	DC low consumption
[Uc] control circuit voltage	48 V DC
Average resistance	5.05 Ohm latching 68 °F (20 °C) 36.36 Ohm unlatching 68 °F (20 °C)
Product Compatibility	CR1F400
Operating time	50...100 ms unlatching 40...75 ms latching
Mechanical durability	1 Mcycles
Maximum operating rate	120 cyc/h 104 °F (40 °C)

Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc

Environment

Net Weight	2.54 lb(US) (1.15 kg)

Ordering and shipping details

Category	18401-WORLD SERVICE PARTS(CTR ACCESS)
Discount Schedule	CP10
GTIN	3389110345513
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	3.5 in (9 cm)
Package 1 Width	3.9 in (10 cm)
Package 1 Length	7.5 in (19 cm)
Package weight(Lbs)	2.47 lb(US) (1.12 kg)

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.