

Product datasheet

Specifications



communication module, PowerLogic P3, Fibre optic, with glass receiver and glass transmitter

REL52818

⚠ Discontinued on: 18 Jun 2026

⚠ Discontinued

Main

Range of product	Easergy P3 VAMP
Accessory / separate part category	Communication accessory
Product or component type	Fibre optic module
Product compatibility	V321

Complementary

Device composition	Glass transmitter Plastic receiver
optic fibre diameter	Glass fibre diameter: 62.5/125 µm Plastic fibre diameter: 1 mm
Communication port protocol	Modbus serial DNP3 IEC 60870-5-103 SPAbus
Operating distance	1000 m for glass fibre 30 m for plastic fibre
Maximum number of supported devices	32
Supply	12 V DC via external supply via RS232 port
Connector type	1 ST connector 1 Versatile Link connector 1 SUB-D connector with 19 pins 1 RS232 connector
Width	62 mm
Height	86 mm
Depth	20 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	6.2 cm
Package 1 Length	7.3 cm
Package 1 Weight	300.0 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No