

# Product datasheet

Specifications



rear connection downside vertical  
mounting - 4 poles - for NT 08..20  
fixed

34100

⚠ Discontinued on: 14 Oct 2021

⚠ End-of-service on: 31 Dec 2021

⚠ Discontinued

## Main

|                                    |                                                                                                                                                                                                       |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                   | MasterPact NT UL 489                                                                                                                                                                                  |
| Product or component type          | Rear connection                                                                                                                                                                                       |
| Accessory / separate part category | Connection accessory                                                                                                                                                                                  |
| Range compatibility                | Masterpact MasterPact NT UL 489 MasterPact NT08 circuit breaker<br>Masterpact MasterPact NT UL 489 MasterPact NT10 circuit breaker<br>Masterpact MasterPact NT UL 489 MasterPact NT12 circuit breaker |
| Poles description                  | 4P                                                                                                                                                                                                    |
| Mounting mode                      | Fixed                                                                                                                                                                                                 |
| [In] rated current                 | 800...1250 A                                                                                                                                                                                          |

## Complementary

|                        |          |
|------------------------|----------|
| Location of connection | Rear     |
| Localisation on device | Downside |
| Connection position    | Vertical |
| Connection pitch       | 70 mm    |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 2 cm   |
| Package 1 Width              | 8 cm   |
| Package 1 Length             | 20 cm  |
| Package 1 Weight             | 1.7 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |