

# Product data sheet

Specifications



## TeSys - LT3TK Thermal time delay protection relay 110 V

LT3TK110

⚠ Discontinued on: May 12, 2023

⚠ Discontinued

### Main

Range of the product	TeSys
Device short name	LT3TK
Product or component type	Relay
Device application	Protection
Relay application	Time delay relay

### Complementary

[Us] rated supply voltage	110 V AC/DC
Voltage range	0.85...1.1 Us
Contacts type and composition	2 C/O multi voltage
[I <sub>th</sub> ] conventional enclosed thermal current	5 A
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Control type	Manual reset Automatic reset
Hold-in power consumption in W	47...51 W
Height	3.3 in (85 mm)
Width	3.2 in (81 mm)
Depth	3.1 in (80 mm)

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.7 in (9.5 cm)
Package 1 Width	5.4 in (13.8 cm)
Package 1 Length	5.4 in (13.8 cm)
Package 1 Weight	20.5 oz (582 g)

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

[EU RoHS Directive](#)

Compliant

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins