

Product data sheet

Specifications



Sedna - double socket-outlet with side earth - 16A shutters, titanium

SDN3000468

! To be discontinued on: 30 December 2023

! To be discontinued

Main

Range name	Sedna
Function	Socket-outlet
Delivery form	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A at 250 V AC

Complementary

Power range	3680 W
Kind of terminals	Lift terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Flexible Solid stranded Rigid
Wire stripping length	13 mm
Material of visible parts	ASA + PC
Surface finish	Glossy
Fixing mode	Claws, span of claws working range: 52...69 mm Screws
Height	120 mm
Width	84 mm
Depth	48 mm
Depth of visual part	23.3 mm
Product weight	0.1031 kg

Environment

Standards	IEC 60884-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	8.500 cm
Package 1 Length	12.000 cm
Package 1 Weight	103.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	10.000 cm
Package 2 Width	20.000 cm
Package 2 Length	31.500 cm
Package 2 Weight	1.138 kg
Unit Type of Package 3	S04
Number of Units in Package 3	50
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	6.032 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)