

Signalling Units

Modular tower lights

Harmony® type XVE Ø 70 mm

Components for beacons and tower lights



Fixing components

Description	Height under base unit mm	Colour	Reference	Weight kg
Plastic fixing bases IP 54 protection (1)	20	Black	XVE Z13	0.040
	100	Black	XVD C02	0.056
Fixing bases comprising: Ø 25 mm aluminium support tube glued into black plastic fixing plate	80	Black aluminium	XVB Z02	0.110
		Aluminium	XVB Z02A	0.110
	380	Black aluminium	XVB Z03	0.200
		Aluminium	XVB Z03A	0.200
	780	Black aluminium	XVB Z04	0.325
		Aluminium	XVB Z04A	0.325

Description	For	Material	Reference	Weight kg
Fixing plate	Ø 25 mm aluminium support tube (to be glued into fixing plate)	Plastic	XVB Z01	0.050
Fixing plate for use on vertical support	Mounting complete and modular tower lights (requires a fixing base)	Zamak	XVB C12	0.380

Separate components for beacons and tower lights

Description	For use with	Composition	Reference	Weight kg
Cover	Complete and modular tower lights	–	XVE Z081	0.010
IP 54 sealing kit	Modular tower lights	5 toric seals for lens units + base unit seal + 1 fixing plate seal + 1 seal for fixing base XVE Z13 + screw fixing cover	XVE Z082	0.015
	Complete tower lights	1 lens unit seal + 1 base unit seal + 2 fixing base seals	XVE Z083	0.005

Description	Electrical characteristics	Sold in lots of	Reference	Weight kg
Incandescent bulbs with BA 15d base fitting for lens units type XVE L3● and XVE C3●	5 W ≈ 24 V	10	DL1 BEBS	0.100
	5 W ≈ 120 V	10	DL1 BEGS	0.100
	5 W ≈ 230 V	10	DL1 BEMS	0.100

(1) IP 54 protection in all mounting positions with XVE Z13. With other fixing bases: IP 54 protection only in vertical position.