

Product datasheet

Specifications



CANopen slave unit, Harmony GTU, for Universal panel

HMIZGCAN

⚠ Discontinued on: 3 Dec 2020

EAN Code: 3606480778674

⚠ Discontinued

Main

Range of product	Harmony GTU
Product or component type	CANopen slave unit

Complementary

Accessory / separate part destination	Universal panel
Power consumption in W	0.7 W
Input voltage	3.3 V DC
Range compatibility	Harmony GTU
Width	60 mm
Height	87 mm
Depth	41 mm
Net weight	0.1 kg

Environment

Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-20...60 °C
Relative humidity	10...90 %
IP degree of protection	IP2
Vibration resistance	3.5 mm constant amplitude (f= 5...9 Hz) conforming to IEC 61131-2 9.8 m/s² (f= 9...150 Hz) conforming to IEC 61131-2
Shock resistance	147 m/s²
Product certifications	IEC-Ex KC CE EAC RCM ATEX zone 2/22

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Use Better

Materials and Substances	
SCIP Number	3ef98c29-b74e-4887-94d0-305f1069929b

Use Longer

Lifetime extension	
Repair	No