

Product data sheet

Specifications



ASCO 5800 Load Bank

ASCOLBLV5800

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

| | |
|-------------------------|---|
| Voltage Rating | 480 V AC 60 Hz, 3 phase |
| Capacity Rating | 3000 kW 2500 kW 2000 kW 1500 kW |
| Load Step Resolution | 50 kW 5 kW |
| Cooling System Rating | 8976779.9 Gal/hr(US) (33980.2 m3/h) |
| Provided Equipment | Switch 3 On-Off LED 2 on LED 1 alarm indication Multi-function meter 1 |
| Ambient Air Temperature | -18...122 °F (-28...50 °C) |
| Enclosure Material | Aluminium Steel |
| Surface Finish | Polyester powder Gray |
| Terminal Connections | Quick |
| Width | 96.0...98.0 in (2438.4...2489.2 mm) |
| Height | 124.5...133.0 in (3162.3...3378.2 mm) |

Environmental

Standards ISO 9001
NEMA

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer

Lifetime extension

Repair **No**