

# Product data sheet

Specifications



## voltage release Compact MN - 48 V AC 50/60Hz

29405

⚠ Discontinued

### Main

Range	ComPact
Range of Product	NSJ400...600 NSF150...250 NB400...600 NR400...630 NS400...630 DC NR100...250 NS100...250 NS100...250 DC NS400...630 NS125E
Device short name	MN
Product or Component Type	Voltage release
Device Application	Control
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48 V AC 50/60 Hz
Range compatibility	ComPact ComPact NS ComPact Compact NB ComPact Compact NR ComPact Compact NSF ComPact Compact NSJ

### Complementary

Operating threshold	0.35...0.7 Un opening 0.85 Un closing
Response time	< 50 ms
Supply holding power	< 5 VA
Auxiliary connection terminal	screw terminal 0...0.002 in <sup>2</sup> (0...1.5 mm <sup>2</sup> )

### Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	00785901110095
Returnability	No

### Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

# Contractual warranty

---

Warranty (in months)

18



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.