

# Product datasheet

Specifications



## TeSys Deca - contactor coil - LX4D7 - 305 V DC standard for 80 A contactor

LX4D7TD

⚠ Discontinued on: Oct 10, 2020 AD

⚠ Discontinued

### Main

Range	TeSys
Product or component type	Contactor coil
Device short name	LX4D7
Control circuit type	DC standard
[Uc] control circuit voltage	305 V DC
Average resistance	4486 Ohm at 20 °C
Product compatibility	LC1D80
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 60 °C

### Complementary

Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.1...0.3 U <sub>c</sub> (at <55 °C) Operational: 0.85...1.1 U <sub>c</sub> (at <55 °C)
Time constant	75 ms
Inrush power in W	22 W (at 20 °C)
Hold-in power consumption in W	22 W at 20 °C

### Environment

Ambient air temperature for operation	-5...60 °C
Net weight	0.68 kg

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

### Contractual warranty

Warranty (in months)	18
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer



#### Lifetime extension

Repair

No