

Product datasheet

Specifications

Motors



AC servo motor BDH - 6 N.m - 6000 rpm - untapped shaft - with brake - IP67

BDH0844J25F2A

⚠ Discontinued on: 8 Jul 2022

⚠ Discontinued

EAN Code: 3389118176478

Main

Product or component type	AC servo motors
Component name	BDH
Continuous stall torque	6 N.m for LXM15LD28M3 3 phases 6 N.m for LXM15MD28N4 3 phases
Peak stall torque	12.18 N.m for LXM15LD28M3 at 230 V 3 phases 12.18 N.m for LXM15MD28N4 at 230 V 3 phases
Nominal output power	1500 W for LXM15LD28M3 at 230 V 3 phases 1500 W for LXM15MD28N4 at 230 V 3 phases
Nominal torque	4 N.m for LXM15LD28M3 at 230 V 3 phases 4 N.m for LXM15MD28N4 at 230 V 3 phases
Nominal speed	3500 rpm for LXM15LD28M3 at 230 V 3 phases 3500 rpm for LXM15MD28N4 at 230 V 3 phases
Maximum mechanical speed	6000 rpm
Product compatibility	LXM15LD28M3 at 230 V 3 phases LXM15MD28N4 at 230 V 3 phases
Shaft end	Untapped
IP degree of protection	IP67
Encoder type	2-pole resolver
Speed feedback resolution	65536 points/turn
Holding brake	With
Mounting support	International IEC standard flange
Electrical connection	Rotatable right-angled connectors
Number of poles	10

Complementary

Range compatibility	Lexium 15
Maximum current Irms	24.89 A
Torque constant	0.69 N.m/A at 120 °C
Back emf constant	44.2 V/krpm at 120 °C
Stator resistance	0.88 Ohm at 20 °C
Stator inductance	3.8 mH at 20 °C
Stator electrical time constant	4.32 ms at 20 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Maximum radial force Fr	310 N at 6000 rpm
	340 N at 5000 rpm
	370 N at 4000 rpm
	400 N at 3000 rpm
	430 N at 2000 rpm
	460 N at 1000 rpm
Maximum axial force Fa	0.3 x Fr
Net weight	5.3 kg



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No