

Product datasheet

Specifications



communication module ProfiNet,
Altivar, 100Mbps, 2 x RJ45
connectors

VW3AP3627

Main

Range of product	Altivar
Product or component type	Communication module
Condition of use	Cannot be ordered alone, only possible in combination with a standard enclosure

Complementary

Range compatibility	Altivar Process ATV900 Altivar Process ATV600
Communication port protocol	PROFINET Link Layer Discovery Protocol
Electrical connection	2 connectors RJ45, Ethernet
Transmission rate	100 Mbps
Web server	Embedded HTTP server
Web services	Data editor Drive monitor Drive recorder Save/restore drive configuration IPar client settings Ethernet statistics Drive parameters
Display type	1 LED for MS (Module Status) 1 LED for NS (Network Status) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for TX/RX (Transmit/Receive port 2)
Bus profile	PROFIdrive
Product weight	0.3 kg

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	9.0 cm
Package 1 Length	6.5 cm
Package 1 Weight	63.0 g

Contractual warranty

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No