

Product datasheet

Specifications



miniature circuit breaker - Domae -
2P - 16A - 220...240 V - C curve -
4.5 kA

DOM11232SNI

⚠ Discontinued on: 30 Mar 2022

⚠ Discontinued

Main

Device application	Distribution
Range	Domae
Product or component type	Miniature circuit-breaker
Poles description	2P
Number of protected poles	2
[In] rated current	16 A
Network type	AC
Curve code	C
Breaking capacity	4500 A at 230 V AC 50 Hz conforming to IEC 60898-1

Complementary

Network frequency	50 Hz
[Ue] rated operational voltage	220...240 V AC 50 Hz
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
Comb busbar and distribution block compatibility	YES
9 mm pitches	4
Colour	Grey

Environment

Standards	SNI 04-6507.1 IEC 60898-1
Product certifications	SNI

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.45 cm
Package 1 Width	3.65 cm
Package 1 Length	8.5 cm

Package 1 Weight

194 g



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Packaging

EU RoHS Directive

[Compliant](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations