

# Product datasheet

Specifications



modular safety transformer - 230 V  
50..60 Hz - output 12..24 V - 16 VA

15218

⚠ Discontinued on: 1 Nov 2020

⚠ Discontinued

## Main

|                           |                    |
|---------------------------|--------------------|
| Transformer type          | Safety transformer |
| Range of product          | TR                 |
| Product or component type | Transformer        |
| Device short name         | TR                 |

## Complementary

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| [Ue] rated operational voltage  | 230 V AC 50/60 Hz                             |
| Output voltage                  | 12/24 V: +/- 5 % on load<br>14/28 V: off load |
| Output short-circuit protection | Built-in                                      |
| rated power in VA               | 16 VA                                         |
| Mounting mode                   | Fixed                                         |
| Mounting support                | 35 mm symmetrical DIN rail                    |
| 9 mm pitches                    | 10                                            |
| Height                          | 89 mm                                         |
| Width                           | 90 mm                                         |
| Depth                           | 60 mm                                         |
| Auxiliary connection terminal   | Tunnel type terminals 4 mm²                   |

## Environment

|                                       |                                           |
|---------------------------------------|-------------------------------------------|
| Standards                             | EN 61558-2-6<br>IEC 61558-2-6<br>EN 60742 |
| Product certifications                | NF                                        |
| Overvoltage category                  | Class II with terminal shields in option  |
| Ambient air temperature for operation | -20...55 °C                               |
| Ambient air temperature for storage   | -25...80 °C                               |

## Packing Units

|                              |      |
|------------------------------|------|
| Unit Type of Package 1       | PCE  |
| Number of Units in Package 1 | 1    |
| Package 1 Height             | 7 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                  |          |
|------------------|----------|
| Package 1 Width  | 9.5 cm   |
| Package 1 Length | 9.5 cm   |
| Package 1 Weight | 1.083 kg |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Longer

| Lifetime extension |    |
|--------------------|----|
| Repair             | No |

### Use Again

| Repack and remanufacture |                                                                                                                                                                                                               |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEEE Label               |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |