

# Product datasheet

Specifications



Ready to close contact (PF),  
MasterPact NT/NW fixed, 1  
changeover contact, low level, 3A/  
240VAC

47343

## Main

Product or component type	Auxiliary contact
Device short name	PF
Range compatibility	Masterpact MasterPact NT Masterpact MasterPact NW
Signal contacts composition	1 NO/NC

## Complementary

Auxiliary contacts type	Low level
Mounting mode	Fixed
Breaking capacity (A)	DC-12: 0.15 A at 250 V DC DC-12: 3 A at 24/48 V DC AC-12: 3 A at 24/48 V AC 50/60 Hz AC-12: 3 A at 240 V AC 50/60 Hz DC-12: 0.3 A at 125 V DC AC-12: 3 A at 380 V AC 50/60 Hz

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	11.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	40.0 g

## Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Packaging

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

Halogen-free status

Halogen free plastic parts product

### Use Longer



#### Lifetime extension

Repair

No

### Use Again



#### Repack and remanufacture

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins