

Product datasheet

Specifications



motor-mechanism - Tm60 3-4P - 230 V 50..60 Hz

18311

⚠ Discontinued on: 5 Apr 2019

⚠ Discontinued

Main

Product or component type	Remote control auxiliary
Device short name	Tm60

Complementary

Control type	Remote control maintained 230 V AC 50/60 Hz Coil deconnection
Response time	1 s (opening) 2 s (closing)
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	7
Height	81 mm
Width	135 mm
Depth	45 mm
Net weight	0.31 kg
Product compatibility	3P DT40 4P DT40 3P + N C60 3P + N DT40 3P DT60 4P DT60 4P C60 3P + N DT60 4P iDPN 3P + N iDPN 3P iDPN 3P C60

Environment

Standards	IEC 60947-2
-----------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	12 cm
Package 1 Length	18 cm
Package 1 Weight	386 g

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins