

# Product data sheet

Specifications



## TeSys LG - enclosed DOL starter - 9 A - 380/400 V AC coil

LG1K095Q7

⚠ Discontinued on: 15 Dec 2021

⚠ Discontinued

### Main

|                                |   |
|--------------------------------|---|
| Range                          | TeSys   |
| Product name                   | TeSys LG  |
| Device short name              | LG1K  |
| Product or component type      | Enclosed DOL starter  |
| Device application             | Safety  |
| Utilisation category           | AC-3  |
| Device composition             | Circuit-breaker ordered separately<br>Contactor<br>Switch disconnecter                    |
| [Ie] rated operational current | 9 A AC-3  |
| [Uc] control circuit voltage   | 380/400 V AC 50/60 Hz   |
| Control type                   | Push-button start white I<br>Push-button stop black O<br>Rotary handle emergency stop red |

### Complementary

|                    |   |
|--------------------|---|
| Cable entry number | 4 2 Pg 13 + 2 Pg 16 top<br>4 2 Pg 13 + 2 Pg 16 bottom |
| Width              | 175 mm  |
| Height             | 165 mm  |
| Depth              | 165 mm  |

### Environment

|                              |                              |
|------------------------------|------------------------------|
| Standards                    | IEC 60947-4-1<br>IEC 60204-1 |
| Material                     | Polycarbonate                |
| IK degree of protection      | IK07 conforming to IEC 60529 |
| IP degree of protection      | IP55 conforming to IEC 60529 |
| Environmental characteristic | Standard environment         |

### Packing Units

|                              |       |
|------------------------------|-------|
| Unit Type of Package 1       | PCE   |
| Number of Units in Package 1 | 1     |
| Package 1 Height             | 18 cm |

---

|                  |         |
|------------------|---------|
| Package 1 Width  | 22.5 cm |
| Package 1 Length | 25.5 cm |
| Package 1 Weight | 1.47 kg |

---

## Contractual warranty

---

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

SCIP Number **7e14df67-eba2-4420-9585-9bffc1c2bbc8**

EU RoHS Directive [Compliant](#)

### Use Longer



#### Lifetime extension

Repair **No**

### Use Again



#### Repack and remanufacture

End of life manual availability [End of Life Information](#)

WEEE Label  **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**