

Product datasheet

Specifications



enclosed DOL starter TeSys - GV2-LC - 14 A

GV2LC0216R

! Discontinued

Main

Range of product	TeSys
Device short name	GV2LC
Motor starter type	Non reversing
Product or component type	Enclosed DOL starter
Poles description	3P
Motor starter composition	With circuit breaker
Trip unit technology	Magnetic
Thermal protection adjustment range	14 A
Control type	Rotary handle red
Enclosure material	Polycarbonate

Complementary

[Ue] rated operational voltage	690 V
Breaking capacity	10 kA Icu at 500 V conforming to IEC 60947-2 100 kA Icu at 220...230 V conforming to IEC 60947-2 20 kA Icu at 440 V conforming to IEC 60947-2 50 kA Icu at 400...415 V conforming to IEC 60947-2
cable entry	2 x 20 mm ISO at top 2 x 25 mm ISO at top 2 x 20 mm ISO at bottom 2 x 25 mm ISO at bottom
Locking options description	Padlock in OFF position 1 to 3 padlocks Ø 8
Width	88 mm
Height	166 mm
Depth	173 mm
Net weight	0.78 kg

Environment

Standards	IEC 60439-1 VDE 0660-102 IEC 60947-4 EN 60947
IP degree of protection	IP54 conforming to IEC 60529

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Longer



Lifetime extension

Repair

No