

# Product datasheet

Specifications



coil, MX/XF/MCH, 380/415 VAC,  
EasyPact NW, fixed

ENW21523

## Main

Range of product	EasyPact NW
Range	EasyPact
Device short name	XF
Product or component type	Closing coil
Device application	Control
Range compatibility	EasyPact EasyPact NW circuit breaker
Voltage release type	Closing coil

## Complementary

Control type	Electrically operated
Control signal type	Maintained
[Uc] control circuit voltage	380/480 V AC 50/60 Hz
Supply holding power	4.5 W 4.5 VA
Mounting mode	Fixed

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	30.0 cm
Package 1 Length	20.0 cm
Package 1 Weight	3.0 kg

## Contractual warranty

Warranty (in months)	18
----------------------	----

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	3 477 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	19 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 446 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and considering quality and safety standards
SCIP Number	3f2d539a-6ab5-46aa-8603-9354f4ae3294
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	68
End of life manual availability	<a href="#">End of Life Information</a>
Take-back	No

Offer Marketing Illustration

Product benefits / Features

---

EasyPact NW



The central image shows a Schneider EasyPact NW circuit breaker unit, a compact, black metal enclosure with a green status bar on top. It is surrounded by six feature callouts:

- NFC connectivity**: Represented by a smartphone icon with a signal wave, indicating wireless communication capabilities.
- Colour-coded health status bar**: A green bar on the top of the unit, with a text box stating it offers easy monitoring and allows for proactive actions.
- Simpler commissioning**: Represented by a checkmark icon, with a text box stating it achieves quick and simple commissioning through EPIC and mobile EPD.
- Innovative front-end retrofit capability**: Represented by a circular arrow icon, with a text box stating it enables upgrades in just 5 minutes, eliminating the need for shutdown.
- Detailed event logs**: Represented by a calendar icon, with a text box stating it facilitates rapid fault diagnosis with easy access to detailed trip event records.
- Compact frame**: Represented by a four-pointed star icon, with a text box stating it optimizes switchboard footprints with a compact frame size, offering a higher breaking capacity of up to 66 kA.