

Product data sheet

Specifications



ASCO 4600 Load Bank

ASCOLBLV4600

⚠ Discontinued on: Nov 20, 2023

⚠ Discontinued

Main

Product Type Resistive load bank

Complementary

Voltage Rating	208 V AC 60 Hz, 3 phase 240/480 V AC 60 Hz, 3 phase 240 V AC 60 Hz, 3 phase 400 V AC 50 Hz, 3 phase 480 V AC 60 Hz, 3 phase 600 V AC 60 Hz, 3 phase
Capacity Rating	500 kW 750 kW 1000 kW 1250 kW
Load Step Resolution	5 kW 50 kW
Cooling System Rating	10323289.0 Gal/hr(US) (39077.2 m3/h)
Provided Equipment	Switch 3 On-Off LED 2 on LED 1 alarm indication Fuse Cooling fans
Enclosure Material	Aluminium Steel
Surface Finish	Polyester powder
Color	Gray
Connection Terminals	Terminals inside)
Length	75.2 in (1911 mm)
Width	84.0 in (2133 mm)
Height	50.5 in (1283 mm)
Product Weight	1800.08 lb(US) (816.5 kg)

Environment

Ambient Air Temperature	-18...122 °F (-28...50 °C)
Standards	ISO 9001 NEMA

Contractual warranty

Warranty (in months) 18

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **No**

Use Longer

Lifetime extension

Repair **No**